

# ILUKON PRO LED PAR 20 DIM

PARA USO GENERAL



CRI  
IRC

80

VIDA Hrs  
LIFE Hrs

15.000

ANGULO  
ANGLE

220°

EFICACIA  
EFFICACY

71lm/w

F. POTENCIA  
POWER FACTOR

≥0,90

VOLTAJE  
VOLTAGE

120V

DIM



**ILUKON**  
PROFESSIONAL LIGHTING



## Especificaciones Fotométricas / Photometric Specifications

Código/ Code	Watts/ Watts	Flujo Luminoso LED/ Luminous Flux LED	Temp. Color / CCT	Voltaje entrada/ Input Voltage	Factor de Potencia/ Power Factor	Vida útil hrs/ Lifetime hrs	Eficiencia/ Efficacy
95020070F	7W	500 Lm	3000 K	120V	0.90	15.000	71 LPW
95002007F	7W	500 Lm	5000 K	120V	0.90	15.000	71 LPW

NOTA: GLS se reserva el derecho de modificar o revisar las especificaciones técnicas sin previo aviso.

NOTE: GLS reserves the right to modify or revise technical specifications without prior notice.

Contacto: [www.gls-ca.com](http://www.gls-ca.com) / mail: [contact@gls/ca.com](mailto:contact@gls/ca.com) / tel: (506) 2434-1212 y (506) 2228-2222.

**GLS**  
GLOBAL LIGHTING  
SOLUTIONS S.A.  
Master Distributor