Q0120GFI

Mini circuit breaker, QO, 20A, 1 pole, 120VAC, 10kA, 6mA grd fault A, pigtail, plug in mount





Main	
Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Ground fault protecting class A 6 mA
Ratings	Not rated
Electrical Connection	Pressure plate

\sim				
Com	വമ	ma	nts	3 F \ /
COLL	σ	1110	πις	ai v

Complementary	
Interrupt Rating	10 kA 120 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 14AWG 8 copper AWG 12AWG 8 aluminium
Tightening Torque	40.71 Lbf.In (4.6 N.m) 0.000.02 in² (2.510 mm²) (AWG 16AWG 14) 40.71 lbf.in (4.6 N.m) 0.010.03 in² (420 mm²) (AWG 12AWG 4)
Height	4.13 in (105 mm)
Width	0.75 in (19 mm)
Depth	2.91 in (74 mm)
Net Weight	0.53 lb(US) (0.240 kg)

Environment

Certifications	UL Listed CSA	
Ambient Rating	104 °F (40 °C)	

Ordering and shipping details

Category	00003-QO 1&2 POLE GFI CB 30A MAX
Discount Schedule	DE2A
GTIN	785901255079
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.30 in (3.302 cm)	
Package 1 Width	3.90 in (9.906 cm)	
Package 1 Length	5.50 in (13.97 cm)	
Package 1 Weight	8.48 oz (240.404 g)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	1824	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 Width	40.00 in (101.6 cm)	

Package 2 Length	48.00 in (121.92 cm)	
Package 2 Weight	994.00 lb(US) (450.87 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	☐ Product Environmental Profile	
Circularity Profile	End Of Life Information	

Contractual warranty

Warranty	18 months
----------	-----------