

# Hoja Técnica

**Product Number:** 49203



**Order Abbreviation:** QTP3X32T8UNVISNSCOSRAM

**General Description:** QTP3x32T8UNVISNSC 3-lamp 32wT8 Instant Start electronic ballast, universal voltage, normal ballast factor, 10-pk

Product Information	
Abbrev. With Packaging Info.	QTP3X32T8UNVISNSCOSRAM
Ballast Factor	0.88
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	3
Open Circuit Voltage (V)	<600V
Power Factor	>0.97
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	-20
Starting Temperature - Celsius	-29
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS
Max Case Temperature	70°C
Total Maximum Wattage	90
Footnotes	

- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Input Frequency: 50/60Hz.
- Minimum starting temperature: -20 F / -29 C

VE TU MUNDO BAJO UNA NUEVA LUZ

